

Newport Panel Meters/Controllers

INFCAC Series

- 4-Digit, 14-Segment LED Display, Red or Green
- High $\pm 0.1\%$ of Reading Accuracy
- Wide Selection of AC Current and Voltage Ranges
- Smart Filtering Detects the Difference Between a Spike or Process Change (Patent Pending)
- Front Panel Configuration
- Available with Dual 6 Amp Relays and/or Analog Output

INFC Series

- Process (DC Voltage and Current), Strain Gauge, Thermocouple, and RTD
- Dual Differential Thermocouple and RTD
- pH ORP
- Relay Output Optional
- Isolated or Non-Isolated Analog Output Optional

IDP Series

- Easy Scaling
- 4-Digit LED Display
- Max or Min Recall
- Short Case 4.1" (104 mm)
- Red or Green LED Display
- Power 115 VAC, 230 VAC or 10–32 VDC

INFC ORDERING INFORMATION

To Order—Insert Number Code for Each Letter to Select Catalog Number.
Order Example: INFCP-5-1-2

A - **B** - **C** - **D**

A	Basic Unit
INFCP	Process (DC Voltage and Current)
INFCS	Strain Input
NIFCT	Thermocouple
INFCDT	Dual/Differential Thermocouple
INFCR	RTD
INFCDR	Dual/Differential RTD
INFCPH	pH
INFCOR	ORP
INFCOP	pH/ORP
B	Power and Display
0	115 VAC, Red LED Display
1	230 VAC, Red LED Display
2	115 VAC, Green LED Display
3	230 VAC, Green LED Display
4	10–32 VDC, Red LED Display
5	10–32 VDC, Green LED Display
6	25–56 VDC, Red LED Display
7	25–56 VDC, Green LED Display
C	Relays
0	None
1	Two 6 Amp Form C Relays
D	Analog Output
0	None
1	Non-Isolated Analog
2	Isolated Analog Output



INFCAC



IDP-0

INFCAC ORDERING INFORMATION

To Order—Insert Number Code for Each Letter to Select Catalog Number.
Order Example: INFCAC-0-0-1-0-V5

A - **B** - **C** - **D** - **E** - **F**

A	Basic Unit
INFCAC	AC Voltage and Current Controller
B	Power and LED Color
0	115 VAC, Red LED Display
1	230 VAC, Red LED Display
2	115 VAC, Green LED Display
3	230 VAC, Green LED Display
C	Control Output
0	No Control Output
1	Two 6A Form "C" Relays
D	Analog Output
0	No Analog Output
1	4 to 20 mA or 0 to 10 VDC
E	Communications
0	No Serial Output
1	Isolated RS-232
2	Isolated RS-485 Half Duplex
F	Input Signal
V5	0–750 VAC User Programmable
C5	0–5 AAC User Programmable

IDP ORDERING INFORMATION

To Order—Insert Number Code for Each Letter to Select Catalog Number.
Order Example: IDP-0

A - **B**

A	Basic Unit
IDP	4-Digit Process Meter
IDT	4-Digit Thermocouple Meter
IDpH	4-Digit pH Meter
B	Display/Power
0	Red/115 VAC
1	Red/230 VAC
2	Green/115 VAC
3	Green/230 VAC
4	Red/10–32 VDC
5	Green/10–32 VDC